



To control your energy,
focus on **HEAT
TRANSFER**



www.barriquand.com



Barriquand

HEAT EXCHANGERS

Barriquand Heat Exchangers designs and develops custom-built optimized thermal solutions, supplying the best heat exchanger technology to cope with your specific applications.



RELIABLE SOLUTIONS

With over 90 years of extensive experience, we offer **high quality products**:

- **Platular®** welded plate heat exchangers
- **Shell & Twist®** and **Shell and tubes** heat exchangers
- **Plate and gaskets** heat exchangers

ENGINEERS SPECIALIZED BY MARKET:



Chemical,
Petrochemical



Oil & Gas



Environment
& Energy



Heavy
industry




Agro-
industry



HVAC



THERMAL EFFICIENCY



DESIGN

Each unit is designed using in-house proprietary software and is continuously monitored by our quality-assurance team throughout the manufacturing process.

CARACTERISTICS

up to 70 tons and 1 500 m²

MATERIALS

304L - 316L - 316TI - 254 SMO - UB6 - 45N - C22 - C 2000 - C276...

CERTIFICATIONS AND CONSTRUCTION CODES

DESP, U STAMP, CODAP, ASME VIII, EN 13445, TEMA, SELO

TESTS

Air - NH₃ - Helium - Demineralized water - Oil - X-Ray - Ultrasound - Roughness...

SURFACE FINISHES

2B finish - Cold rolling - Mechanical polishing - Electro-polishing - Oxygen degreasing...

PLATULAR®

WELDED PLATE HEAT EXCHANGERS

PLATULAR® HYBRID AND EASY-TO-CLEAN HEAT EXCHANGER

Wide gap welded plate units specially designed to counter fouling problems related to complex fluids (viscous, containing a high content of suspended matter...)




ADVANTAGES OF THIS PATENTED TECHNOLOGY

- Highly flexible **custom-built solutions**
- **Clear free flow channels** for dirty, complex or viscous fluids
- **High heat exchange** coefficient with a tight temperature approach
- **High temperature crosses** possible
- **Fully welded** = Gasket-free design
- Compact and Robust thanks to Barriquand's patented **design**
- **Low operating costs** = more savings
- Openable and accessible via **hinged access covers** for **easy maintenance** in situ
- **Quick process shut down** for maintenance / inspection duties
- **Reduced cleaning frequency** thanks to clear free-flow channels without contact points

CHANNEL PROFILES

Spacing from 3 to 40 mm
Optimized pressure drop
Plate thickness: 1.5 to 3 mm






HEAT TRANSFER CONDITIONS

Heater
Cooler
Condenser
Liquid x Liquid
Gas x Liquid
Gas x Gas
Vapor
Steam



VARIOUS DESIGNS AVAILABLE

- Fully welded construction: **XS, JS**
- Hinged access covers on 1 circuit: **XASP**
- Hinged access covers on 2 circuits: **XP**
- Overhead Column Condensers





BARRIQUAND HEAT EXCHANGERS REPRESENTATIVE / OFFICES



HEAD OFFICE

9-13 rue Saint Claude | 42300 ROANNE | France

+33(0)4 77 44 22 20

export@barriquand.com

www.barriquand.com